

Silver & Deming Drills

WESTHOFF
Industrial Tool & Supply



Silver & Deming Drills - 1/2" Shank



Type 280

This general purpose 118° HSS drill is recommended for use in portable air and electric drilling equipment with 1/2" chucks. Type 280 drills may be used in power applications such as drill presses where a short rigid drill is required.

Dia. (in.)	Order No.	Our Price
33/64	29130V	13.39
17/32	29140V	12.76
35/64	29150V	14.26
9/16	29160V	13.58
37/64	29170V	15.30
19/32	29180V	14.58
39/64	29190V	16.03
5/8	29200V	15.79
41/64	29210V	17.12
21/32	29220V	16.30
43/64	29230V	17.78
11/16	29240V	16.93
45/64	29250V	18.85
23/32	29260V	17.95
47/64	29270V	19.83
3/4	29280V	18.69
49/64	29290V	20.82
25/32	29300V	19.83
51/64	29310V	20.83
13/16	29320V	20.83
53/64	29330V	21.75
27/32	29340V	21.75
55/64	29350V	22.57
7/8	29360V	22.57
57/64	29370V	23.58
29/32	29380V	23.58
59/64	29390V	25.25
15/16	29400V	25.25
61/64	29410V	26.64
31/32	29420V	26.64
63/64	29430V	29.40
1	29440V	29.40
1-1/16	29450V	34.30
1-1/8	29460V	39.26
1-5/32	29470V	43.05
1-3/16	29480V	43.05
1-1/4	29490V	47.66

**280-UB Drills
feature 3
Flats on
the
Shank**

Ultra Cut Super Premium Type 280-UB

- Special Hi-Molybdenum tool steel.
- 135° split point for fast penetration and accurate starting without a center punch
- Precision ground point, flutes, body, clearance and drill diameter for the ultimate in accuracy and performance.
- Space age nitro-carburized steel withstands substantially higher drilling temperatures while maintaining sharpness.
- **Recommended for use in work hardening grades of stainless steel and other hard drilling applications.**

Diam. (in.)	Order No.	Our Price
33/64	29550V	15.97
17/32	29560V	15.22
35/64	29570V	17.02
9/16	29580V	16.21
37/64	29590V	18.27
19/32	29600V	17.41
39/64	29610V	19.13
5/8	29620V	18.25
41/64	29630V	20.42
21/32	29640V	19.44
43/64	29650V	21.22
11/16	29660V	20.20
45/64	29670V	22.48
23/32	29680V	21.40
47/64	29690V	23.42
3/4	29700V	22.36
49/64	29710V	24.84
25/32	29720V	23.67
51/64	29730V	24.86
13/16	29740V	24.86
53/64	29750V	25.95
27/32	29760V	25.95
55/67	29770V	26.94
7/8	29780V	26.94
57/64	29790V	28.14
29/32	29800V	28.14
59/64	29810V	30.12
15/16	29820V	30.12
61/64	29830V	36.80
31/32	29840V	31.80
63/64	29850V	35.08
1	29860V	35.08
1-1/32	29870V	46.32
1-1/16	29880V	42.41
1-1/32	29890V	51.17
1-1/8	29900V	46.39
1-5/32	29910V	48.33
1-3/16	29920V	49.40
1-7/32	29930V	62.66
1-1/4	29940V	54.41
1-5/16	29950V	76.41
1-3/8	29960V	77.38
1-7/16	29970V	86.44
1-1/2	29980V	88.60

8pc. set

Size Range: 9/16 thru 1" by 16ths

Order No. 43200V ONLY \$138.30

← **Type 280**

Type 280-UB



8pc. set

Size Range: 9/16 thru 1" by 16ths

Order No. 92400V **Only \$167.88**

4pc. set

Sizes: 9/16, 5/8, 3/4, 1"

Order No. 12250V **Only \$73.63**